

BC-MS211X

Wholesaler FOB Price: 470\$/pcs

Items	Specification	Material/Size	Functionality	Color
Frames	946*500*90mm	Aluminum alloy	with light	
Seat Cushions	565*400mm	PVC outer skin + PU foam padding, with adjustable armrests	Foldable	Black
Backrests	420*305mm	PVC outer skin + PU foam padding	Foldable	Black
Front Wheel	Diameter 210mm	Wheel, 6" black PU		Black
Rear Wheel	Diameter 210mm	Wheels, 9" black PU		Black
Brakes	Braking distance	≤ 1500mm		
Static Stabilisation		≥ 9°, < 15°		
Dynamic Stabilisation		≥ 6°, < 10°		
Controller		45A		
Battery Pack	Capacity	8Ah*1; 8Ah*2 10ah*1; 10Ah*2	Removable	Black
Drive Motor	power (output)	24V, 270W (Maotian Brushless Motor)		
Vehicle Speed		8km/h		
Charger		24V 2A		Black
Theoretical mileage		20-30km	±25%	
Folding method		Manual folding		
Folding size		Dimensions: 30*50*74cm		
Packing specification		Dimensions: 35*53*76cm		
Packing Quantity		20GP: 180 40HQ: 440		



Size Specification

Description	Overall length	Overall height	Rear wheel width	Backrest height	Seat width	Seat height	Seat depth	Armrests height	Load capacity	N.W. (270w Brushless motors)	N.W. (200w Brushless motors)
Size (mm)	946mm	900mm	505mm	330mm	380mm	520mm	320mm	200mm	≤100kg	17KG	16KG

Description	Distance from footrest to seat	Armrest to seat distance	Horizontal position of the shaft	Minimum Turning Radius	Maximum controller output current	Maximum charger output current	Chassis height	G.W.
Size (mm)	350mm	200mm	732mm	≤1100mm	45A	2A	90mm	23KG